

PROFILE 300WW

Profile 300WW is a 300Watt powered warm white 3200K LED profile spot(ellipsoidal). A fixture design for theatre and studio use. Fixed lens 19°, 26°, 36°, 50° optional. It equipped with HD optics and four shutters to control the shape of the light. Fixture also come with powercon in & out connector. Color temperature also available at cool white 5600K.

Key Features:

- 300Watt COB white LED source
- Warm white 3200K color temperature
- High CRI 97, R9≥90, TLCI up to 98
- HD optical system, clean shutter cuts beam effect
- 19°, 26°, 36°, 50° fixed lens optional
- Smooth dimming, flicker free for all application
- Menu, DMX control of dimmer
- Super silent operation for studio and theatre use
- Die-cast aluminum housing, robust construction
- Also available at 5600K color temperature*



Physical

Length: 700 mm (27.6 in.)
 Width: 270 mm (10.6 in.)
 Height: 263 mm (10.4 in.)
 Net Weight: 9.2 kg (20.2 lb.)

Source

Light source: 300W COB LED
 Color temperature: 3200K or 5600K optional
 Lens: 19°, 26°, 36°, 50° lens optional
 LED lifetime: 50,000 hours avg.*

*LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

Effects

Electronic shutter effect: Instant open and blackout
 Electronic dimming: 0 – 100%
 Strobe and pulse effects: Variable speed and action, random strobe

Control and Programming

Control options: DMX512, RDM
 DMX channels: 1/2/3
 DMX address setting: Control panel with LED display or via RDM
 DMX compliance: USITT DMX512-A

Connection

AC power in / thru: PowerCon in & out
 DMX & RDM data in / thru: 3-Pin XLR in & out

Electrical

AC power: 100–240 V nominal, 50/60 Hz

Power supply unit: Auto ranging power unit

Construction

Housing: Die-cast aluminum
 Colour: Black
 Enviroment: IP20

Thermal

Cooling: Forced ventilation with fans
 Maximum ambient temperature: 40°C Minimum ambient temperature: -10°C

Accessories

Included: Power cable, Color frame, Manual